

# Dominator™ Series

TIR3™ SUPER-LED® TRAFFIC ADVISOR™ AND WARNING MODULES  
FOR INTERIOR OR EXTERIOR USE



D4BRBR



D2RC



D6RBAABR



D800800 / TAD8

***Small size and fully waterproof design make the Dominator the versatile answer to all your secondary warning and signaling needs.***

Available as a six or eight light array Traffic Advisor, or in two, four, six and eight light array flashing models, Dominator features super bright TIR3 Super-LEDs housed in a rugged aluminum housing. Compact enough even for special use vehicles, motorcycles, quads and marine applications, this small but powerful Dominator is the solution to your unique warning light requirements.

## FEATURES

- Incredibly bright TIR3 Super-LED modules.
- Internal self-contained electronics.
- Fully encapsulated, fully waterproof.
- Molex waterproof connectors.
- Many Scan-Lock™ Flash patterns.
- Small diameter 4 or 6 conductor #20 AWG wires.
- Slide bolt mount, standard.
- Optional suction cup, "L" brackets or swivel bracket mounting.
- Size: 1-3/4" (44mm) H x 2-3/16" (60mm) D x 7" (178mm) or 14" (356mm) or 21" (533mm) or 28" (711mm) L.

## Flashing Models

- Two, four, six and eight light flashing arrays.
- Seven flash patterns and a steady-on mode.
- Dominator pairs may be synchronized to each other or to other Whelen synchronizing products.

## Traffic Advisor Models

- Six or eight light array.
- Six light array with two end flashing modules.
- Six direction sequences and 10 Scan-Lock flash patterns.
- Low power (intensity) mode.
- Requires customer supplied switches or Whelen's optional control head (with blanks for optional switches available for other warning light requirements).



Optional TADCTL1



***All Whelen Products  
are proudly made  
in the U.S.A***



*Available in  
4 safety colors*

Form# DOM0504

**WHELEN®**  
Engineers for the Emergency Warning Industry

# DOMINATOR™ SPECIFICATIONS

## FLASHER FEATURES

Waterproof design  
 Low profile aluminum extrusion  
 Self-contained electronics  
 Standard 2 wire TIR3™ Super-LED® lamp modules  
 2, 4, 6 and 8 LED array models.  
 Four safety colors  
 Scan-Lock™ flash patterns  
 Synchronizable  
 Thin 4-conductor #20 AWG 12" cable  
 12 VDC  
 Ground  
 Sync  
 Scan-Lock

## FLASHER FLASH PATTERNS

|              |                     |         |
|--------------|---------------------|---------|
| SignalAlert™ | 1-2-3-4 alt 5-6-7-8 | Phase 1 |
| CometFlash®  | 1-2-3-4 alt 5-6-7-8 | Phase 2 |
| DoubleFlash  | 1-2-7-8 alt 3-4-5-6 | Phase 1 |
| SingleFlash  | 1-2-7-8 alt 3-4-5-6 | Phase 2 |
| ComAlert™    | 1-2-3-4-5-6-7-8     |         |
| Phase 1      |                     |         |
| Random*      | 1-2-3-4-5-6-7-8     |         |
| Phase 2      |                     |         |
| ZigZag*      |                     |         |
| Steady*      |                     |         |

(\*non sync patterns)

## FLASHER MODELS

**D2 \*\*:** Two LED modules  
**D4\*\*\*\*:** Four LED modules  
**D6\*\*\*\*\*:** Six LED modules  
**D8\$\$\$\$\$:** Eight LED modules

\*Replace symbol in model number with letter indicating lens color desired:

A=Amber; B=Blue; C=Clear; R=Red

Replace \$ symbol with number of colored LED lightheads required. Order of colors are red, blue, amber and white.

## FLASHER MOUNTING OPTIONS

**DBKT1** Suction cup mount bracket and cigar plug cord for D2 Series, customer installed  
**DBKT2** Two suction cup mount brackets and cigar plug cord for D4 Series, customer installed  
**DBKT3** Swivel mount bracket for D2 and D4 Series, customer installed  
**DBKT4** "L" angle mounting bracket kit (2 brackets), customer installed.



DBKT1



DBKT2



DBKT3

## TRAFFIC ADVISOR™ FEATURES

Waterproof design  
 Low profile aluminum extrusion  
 Self-contained electronics  
 6 and 8 LED array models.  
 Standard TIR3 Super-LED lamp modules  
 Scan-Lock flash patterns  
 Low power control  
 Thin 6 conductor #20 AWG 15' cable

## TRAFFIC ADVISOR PATTERNS

### Direction Sequences

Sequence Triple Flash  
 Sequence On/Sequence Off  
 Sequence On Double Sweep  
 DoubleSweep™  
 Sequence to Solid  
 6 lamp Traffic Advisor with end flasher

### Flasher Patterns

CometFlash® 75  
 DoubleFlash 120  
 DoubleFlash 75  
 SingleFlash375  
 SingleFlash 150  
 SingleFlash75  
 ComAlert 75  
 ActionFlash™ 756  
 ModuFlash™  
 SignalAlert™ 75

## TRAFFIC ADVISOR MODELS

**TAD6:** Six amber LED modules  
**TAD8:** Eight amber LED modules  
**TAD8\*\*** Six amber LED modules with two end flashing modules.

## TRAFFIC ADVISOR OPTIONS

**TADCTL1:** Control head  
**TADSW1:** On/Off, non-lighted 20 amp switch  
**TADSW2:** On/Off/On, non-lighted 20 amp switch  
**TADSW3:** Momentary, non-lighted 20 amp switch  
**DBKT4** "L" angle mounting bracket kit (2 brackets), customer installed.

\*Replace symbol in model number with letter indicating lens color desired:

A=Amber; B=Blue; C=Clear; R=Red



TADCTL1



TADSW2

**WHELEN**®  
 ENGINEERING COMPANY, INC.

Route 145, Winthrop Road  
 Chester, Connecticut 06412-0684  
 (860) 526-9504 • Fax: (860) 526-4078  
 Internet: www.whelen.com



*Whelen Engineering reserves the right to upgrade and improve products without notice.*