

L53 Series


360° Super-LED® Self-contained Beacon



L53 Series, SAE Class 3 Super-LED secondary warning beacon with SignalAlert™ flash pattern.

L53 features exclusive side-emitting LED technology that rivals strobe in intensity with lower amp draw.

LED light source has a rated life that exceeds that of comparable flash tubes by more than 100:1.



Whelen Engineering reserves the right to upgrade and improve products without notice.



Available in Amber

Form# L530604

© 2004 Whelen Engineering Co., Inc. Printed in U.S.A.
Code No. 11619A-0704

FEATURES

- SAE Class 3 LED intensity, while using a single Super-LED.
- 100,000 hour rated life.
- 12 VDC with low current draw (0.15 Amp avg. @ 12.8 VDC).
- Compact size, universal application.
- LED beacon design features SignalAlert™ flash pattern, built-in.
- Supplied with 6" pigtail (permanent mount) or 8' cord with cigar plug and on/off switch with LED "on" indicator (magnetic mount).
- Polycarbonate base and dome.

MODEL

L53AP: Permanent mount, amber beacon.

L53AM: Magnetic mount, amber beacon.

REPLACEMENT PARTS

D1500A: Amber dome

Due to variations in vehicle surfaces and operating conditions, the use of any magnetic mounted warning beacon on the vehicle while in motion is at the discretion and risk of the user.



All Whelen Products
are proudly made
in the U.S.A.

WHELEN
ENGINEERING COMPANY, INC.®

Route 145, Winthrop Road
Chester, Connecticut 06412-0684
(860) 526-9504 • Fax: (860) 526-4078
Internet: www.whelen.com